



### Çalışma Limitleri

d1	10-100mm
p	10 bar(Max)
t	-20/+120 °C
Vg	15 m/s

### Yüzey Seçenekleri

**Döner Eleman:** Karbon, Silisyum Karbür  
**Sabit Eleman:** Seramik, Silisyum Karbür, Krom Nikel  
**Elastomerler:** Viton(FKM), EPDM, NBR

### Çalışma Ortamı

Temiz Su, atık su, yağ ve orta dereceli asidik sıvı

## ÖLÇÜLER

d	D3	D6	D7	L3	L4
10	20.05	17	21	23.9	8.6
12	21.70	19	23	23.9	8.6
14	24.50	21	25	26.4	8.6
16	26.65	23	27	26.4	8.6
18	30.35	27	33	27.5	10.0
20	31.75	29	35	27.5	10.0
22	33.55	31	37	27.5	10.0
24	38.30	33	39	30.0	10.0
25	38.30	34	40	30.0	10.0
28	42.20	37	43	32.5	10.0
30	43.95	39	45	32.5	10.0
32	45.70	42	48	32.5	10.0
33	46.75	42	48	32.5	10.0
35	49.10	44	50	32.5	10.0
38	52.40	49	56	34.0	11.0
40	55.70	51	58	34.0	11.0
43	58.80	54	61	34.0	11.0
45	61.20	56	63	34.0	11.0
48	64.35	59	66	34.0	11.0
50	67.35	62	70	34.5	13.0
53	70.65	65	73	34.5	13.0
55	71.65	67	75	34.5	13.0
58	78.40	70	78	39.5	13.0
60	78.40	72	80	39.5	13.0
63	81.50	75	83	39.5	13.0
65	84.30	77	85	39.5	13.0
68	89.65	81	90	37.2	15.3
70	89.65	83	92	44.7	15.3
75	96.80	88	97	44.7	15.3
80	104.00	95	105	44.3	15.7
85	107.95	100	110	44.3	15.7
90	111.10	105	115	49.3	15.7
95	119.00	110	120	49.3	15.7
100	124.00	115	125	49.3	15.7