



Çalışma Limitleri

d1	10-75 mm
p	10 bar (Max)
t	-20/+180 °C
Vg	15 m/s

Yüzey Seçenekleri

Döner Eleman: Karbon, Silisyum Karbür , Tungsten Karbür
Sabit Eleman: Silisyum Karbür, Tungsten Karbür, Krom Nikel
Elastomerler: Viton(FKM) ,EPDM NBR

Çalışma Ortamı

Temiz Su, atık su, yağ ve orta dereceli asidik sıvı

ÖLÇÜLER

d	D3	D6	D7	D8	L3	L4	L8
10	20	17	21	3	16.9	10.0	17.5
12	22	19	23	3	17.4	10.0	17.5
14	24	21	25	3	17.4	10.0	17.5
16	26	23	27	3	19.5	10.0	17.5
18	31	27	33	3	20.5	11.5	19.5
20	34	29	35	3	22.0	11.5	19.5
22	36	31	37	3	23.5	11.5	19.5
24	38	33	39	3	25.0	11.5	19.5
25	39	34	40	3	26.5	11.5	19.5
28	42	37	43	3	26.5	11.5	19.5
30	44	39	45	3	25.0	11.5	19.5
32	46	42	48	3	28.5	11.5	19.5
33	47	42	48	3	-	11.5	19.5
35	49	44	50	3	28.5	11.5	19.5
38	54	49	56	4	32.2	14.0	22.0
40	56	51	58	4	34.7	14.0	22.0
43	59	54	61	4	-	14.0	22.0
45	61	56	63	4	39.2	14.0	22.0
48	64	59	66	4	44.7	14.0	22.0
50	66	62	70	4	45.7	15.0	23.0
53	69	65	73	4	-	15.0	23.0
55	71	67	75	4	49.0	15.0	23.0
58	78	70	78	4	52.0	15.0	23.0
60	79	72	80	4	53.0	15.0	23.0
63	83	75	83	4	-	15.0	23.0
65	85	77	85	4	54.3	15.0	23.0
68	88	81	90	4	55.3	18.0	26.0
70	90	83	92	4	56.3	18.0	26.0
75	98	88	97	4	56.3	18.0	26.0