



### Çalışma Limitleri

d1	18 - 100 mm
p	16 bar, (Max 25 bar)
t	-20/+180 °C
Vg	15 m/s

### Yüzey Seçenekleri

**Döner Eleman:** Karbon, Silisyum Karbür , Tungsten Karbür  
**Sabit Eleman:** Silisyum Karbür, Tungsten Karbür, Krom Nikel  
**Elastomerler:** Viton(FKM) ,EPDM ,NBR

### Çalışma Ortamı

Temiz Su, atık su, yağ ve orta dereceli asidik sıvı

## ÖLÇÜLER

d	D6	D7	D3	D8	L3	L4	L8
18	27	33	33	3	38	11.5	19.5
20	29	35	35	3	38	11.5	19.5
22	31	37	37	3	38	11.5	19.5
24	33	39	39	3	38	11.5	19.5
25	34	40	40	3	38	11.5	19.5
28	37	43	43	3	39	11.5	19.5
30	39	45	45	3	39	11.5	19.5
32	42	48	47	3	39	11.5	19.5
33	42	48	48	3	39	11.5	19.5
35	44	50	50	3	39	11.5	19.5
38	49	56	55	4	41	14.0	22.0
40	51	58	57	4	42	14.0	22.0
43	54	61	60	4	42	14.0	22.0
45	56	63	62	4	42	14.0	22.0
48	59	66	65	4	42	14.0	22.0
50	62	70	67	4	43	15.0	23.0
53	65	73	70	4	43	15.0	23.0
55	67	75	72	4	43	15.0	23.0
58	70	78	79	4	56	15.0	23.0
60	72	80	81	4	56	15.0	23.0
63	75	83	84	4	55	15.0	23.0
65	77	85	86	4	55	15.0	23.0
68	81	90	89	4	55	18.0	26.0
70	83	92	91	4	56	18.0	26.0
75	88	97	99	4	56	18.0	26.0
80	95	105	104	4	56	18.2	26.2
85	100	110	109	4	56	18.2	26.2
90	105	115	114	4	56	18.2	26.2
95	110	120	119	4	56	17.2	25.2
100	115	125	124	4	56	17.2	25.2