



Çalışma Limitleri

d1	10-100 mm
p	18 bar (Max)
t	-20/+120 °C
Vg	15 m/s

Yüzey Seçenekleri

Döner Eleman: Karbon, Silisyum Karbür
Sabit Eleman: Seramik, Silisyum Karbür
Elastomerler: Viton(FKM) ,EPDM ,Nitril (NBR)

Çalışma Ortamı

Temiz Su, atık su, yağ ve orta dereceli asidik sıvı

ÖLÇÜLER

Size Metric)	d	D3	D6	D7	L3	L31	L32	L4
10	10	20	15	21	15	27.5	35.0	5.0
12	12	22	17	23	15	26.5	34.0	6.0
14	14	24	19	25	15	29.0	34.0	6.0
15	15	25	20	26	15	29.0	34.0	6.0
16	16	26	23	27	15	29.0	34.0	6.0
18	18	32	25	33	20	31.5	39.0	6.0
20	20	34	27	35	20	31.5	39.0	6.0
22	22	36	29	37	20	31.5	39.0	6.0
24	24	38	31	39	20	34.0	44.0	6.0
25	25	39	32	40	20	34.0	44.0	6.0
28	28	42	35	43	26	36.5	44.0	6.0
30	30	44	37	45	26	35.5	43.0	7.0
32	32	46	40	48	26	35.5	48.0	7.0
33	33	47	40	48	26	35.5	48.0	7.0
35	35	49	42	50	26	34.5	47.0	8.0
38	38	54	47	56	30	37.0	47.0	8.0
40	40	56	49	58	30	37.0	47.0	8.0
43	43	59	52	61	30	37.0	52.0	8.0
45	45	61	54	63	30	37.0	52.0	8.0
48	48	64	57	66	30	35.0	50.0	10.0
50	50	66	60	70	30	37.5	50.0	10.0
53	53	69	63	73	30	37.5	60.0	10.0
55	55	71	65	75	30	37.5	60.0	10.0
58	58	78	68	78	33	42.5	60.0	10.0
60	60	80	70	80	33	40.5	58.0	12.0
63	63	83	73	83	33	40.5	58.0	12.0
65	65	85	75	85	33	40.5	68.0	12.0
68	68	88	79	90	33	40.5	68.0	12.0
70	70	90	81	92	33	48.0	68.0	12.0
75	75	99	86	97	40	48.0	68.0	12.0
80	80	104	92	105	40	47.5	77.5	12.5
85	85	109	97	110	40	47.5	77.5	12.5
90	90	114	102	115	40	52.5	77.5	12.5
95	95	119	117	120	40	52.5	77.5	12.5
100	90	124	122	125	40	52.5	77.5	12.5