



Çalışma Limitleri

d1	16-120mm
p	14 bar(Max)
t	-40/+150 °C
Vg	13 m/s

Yüzey Seçenekleri

Döner Eleman: Karbon, Silisyum Karbür , Tungsten Karbür
Sabit Eleman: Seramik, Silisyum Karbür, Tungsten Karbür, Krom Nikel
Elastomerler: Viton(FKM) ,EPDM ,Nitril

Çalışma Ortamı

Temiz Su, atık su, yağ ve orta dereceli asidik sıvı

ÖLÇÜLER

Inch	d	D3	D6	D7	L3	L4
3/8 "	9.5	28	11.0	24.60	25	8.7
1/2 "	12.7	32	13.5	27.80	25	8.7
5/8 "	15.8	35	17.0	30.95	25	10.3
3/4 "	19.0	40	20.0	34.15	25	10.3
7/8 "	22.2	43	23.0	37.30	25	10.3
1 "	25.4	47	26.5	40.50	25	10.3
1 1/8 "	28.5	56	29.5	47.65	33	11.9
1 1/4 "	31.7	59	32.5	50.80	33	11.9
1 3/8 "	34.9	63	36.5	54.00	33	11.9
1 1/2 "	38.1	67	39.5	57.15	33	11.9
1 5/8 "	41.2	71	42.5	60.35	33	11.9
1 3/4 "	44.4	74	46.0	63.50	41	11.9
1 7/8 "	47.6	77	49.0	66.70	41	11.9
2 "	50.8	81	52.0	69.85	41	13.5
2 1/8 "	53.9	84	55.5	73.05	41	13.5
2 1/4 "	57.1	88	58.5	76.20	41	13.5
2 3/8 "	60.3	91	61.5	79.40	41	13.5
2 1/2 "	63.5	94	65.0	82.55	41	13.5