



Çalışma Limitleri

d1	14- 100 mm
p	12 bar (Max)
t	-20/+180 °C
Vg	15 m/s

Yüzey Seçenekleri

Döner Eleman: Karbon, Silisyum Karbür ,
Sabit Eleman: Silisyum Karbür, Krom
 Nikel
Elastomerler: Viton(FKM) ,EPDM ,Nitril
 NBR

Çalışma Ortamı

Temiz Su, atık su, yağ ve orta
 dereceli asidik sıvı

ÖLÇÜLER

d	D3	D6	D7	L3	L4	L8
14	24	21	25	23.0	12.0	12.8
16	26	23	27	23.0	12.0	12.8
18	32	27	33	24.0	13.5	14.5
20	34	29	35	24.0	13.5	14.5
22	36	31	37	24.0	13.5	14.5
24	38	33	39	26.7	13.3	14.3
25	39	34	40	27.0	13.0	14.0
28	42	37	43	30.0	12.5	13.5
30	44	39	45	30.5	12.0	13.0
32	46	42	48	30.5	12.0	13.0
33	47	42	48	30.5	12.0	13.0
35	49	44	50	30.5	12.0	13.0
38	54	49	56	32.0	13.0	14.0
40	56	51	58	32.0	13.0	14.0
43	59	54	61	32.0	13.0	14.0
45	61	56	63	32.0	13.0	14.0
48	64	59	66	32.0	13.0	14.0
50	66	62	70	34.0	13.5	14.5
53	69	65	73	34.0	13.5	14.5
55	71	67	75	34.0	13.5	14.5
58	78	70	78	39.0	13.5	14.2
60	80	72	80	39.0	13.5	14.2
63	83	75	83	39.0	13.5	14.2
65	85	77	85	39.0	13.5	14.2
68	88	81	90	39.0	13.5	14.2
70	90	83	92	45.5	14.5	15.2
75	95	88	97	45.5	14.5	15.2
80	104	95	105	45.0	15.0	15.7
85	109	100	110	45.0	15.0	15.7
90	114	105	115	50.0	15.0	15.7
95	119	110	120	50.0	15.0	15.7
100	124	115	125	50.0	15.0	15.7