



### Çalışma Limitleri

d1	10 - 100 mm
p	10 bar(Max)
t	-20/+180 °C
Vg	15 m/s

### Yüzey Seçenekleri

**Döner Eleman:** Cr-Ni

**Sabit Eleman :** Karbon

**Elastomerler:**Viton(FKM) ,EPDM , NBR

### Çalışma Ortamı

Temiz Su, Atık su, yağ ve diğer orta dereceli asidik sıvılar

## ÖLÇÜLER

d	D3	D6	D7	D8	L31	L4	L7
10	19	17	21	3	25.5	7	8.5
12	20	19	23	3	25.5	7	8.5
14	23	21	25	3	28	7	8.5
16	26	23	27	3	28	7	8.5
18	29	27	33	3	27.5	10	9
20	31	29	35	3	27.5	10	9
22	33	31	37	3	27.5	10	9
24	35	33	39	3	30	10	9
25	36	34	40	3	30	10	9
28	40	37	43	3	32.5	10	9
30	43	39	45	3	32.5	10	9
32	46	42	48	3	32.5	10	9
33	46	42	48	3	32.5	10	9
35	49	44	50	3	32.5	10	9
38	53	49	56	4	32	13	9
40	56	51	58	4	32	13	9
43	59	54	61	4	32	13	9
45	61	56	63	4	32	13	9
48	64	59	66	4	32	13	9
50	66	62	70	4	33.5	14	9
53	69	65	73	4	33.5	14	9
55	71	67	75	4	33.5	14	9
58	76	70	78	4	38.5	14	9
60	78	72	80	4	38.5	14	9
63	81	75	83	4	38.5	14	9
65	84	77	85	4	38.5	14	9
68	87	81	90	4	36.5	16	9
70	89	83	92	4	44	16	9
75	98	88	97	4	44	16	9
80	100	95	105	4	42	18	9
85	107.5	100	110	4	42	18	9
90	110	105	115	4	47	18	9
95	119	110	120	4	47	18	9
100	123.8	115	125	4	47	18	9