



Çalışma Limitleri

d1	25 - 55 mm
p	16 bar(Max)
t	-20/+220 °C
Vg	20 m/s

Yüzey Seçenekleri

Döner Eleman: Karbon, Silisyum Karbür , Tungsten Karbür

Sabit Eleman :Seramik,Silisyum Karbür, Tungsten Karbür, Krom Nikel

Elastomerler:Viton(FKM) ,EPDM ,Nitril

Çalışma Ortamı

Temiz Su,atık su, yağ ve orta dereceli asidik sıvı

ÖLÇÜLER

Qd	D1	L	F	D2	D3
18	36	43	6.0	24.0	30.0
20	38	43	6.0	29.5	35.0
22	40	43	6.0	29.5	35.0
24	42	43	6.0	32.0	38.0
25	43	43	6.0	32.0	38.0
28	46	45	7.0	36.0	42.0
30	48	47	7.0	39.2	45.0
32	50	49	7.5	42.2	48.0
35	53	49.5	7.5	46.2	52.0
38	59	55.3	7.5	49.2	55.0
40	62	55.3	7.5	52.2	58.0
42	64	62.3	7.5	53.3	62.0
45	67	62.3	8.0	55.3	64.0
48	69	65.3	8.0	59.7	68.4
50	72	69.3	8.0	60.8	69.3
55	77	70.3	8.0	66.5	75.4
58	80	72.3	8.0	69.5	78.4
60	82	74.3	8.0	71.5	80.4
65	90	76.3	9.0	76.5	85.4