



### Çalışma Limitleri

d1	16-100 mm
p	20 bar (Max)
t	-45/+200 °C
Vg	15 m/s

### Yüzey Seçenekleri

**Döner Eleman:** Karbon, Silisyum Karbür , Tungsten Karbür  
**Sabit Eleman:** Silisyum Karbür, Tungsten Karbür, Krom Nikel  
**Elastomerler:** Viton(FKM) ,EPDM ,NBR

### Çalışma Ortamı

Petrol, rafine edilmiş yağlar ,

## ÖLÇÜLER

d	D3	D6	D7	L3	L4	L8	d8
16	30.0	23	27	32.5	10.0	17.5	3
18	32.0	27	33	30.5	7.0	14.0	3
20	33.5	29	35	30.5	7.0	14.0	3
22	36.5	31	37	30.5	7.0	14.0	3
24	39.0	33	39	28.5	11.5	19.5	3
25	39.6	34	40	28.5	11.5	19.5	3
28	42.8	37	43	31.0	11.5	19.5	3
30	45.0	39	45	31.0	11.5	19.5	3
32	46.0	42	48	31.0	11.5	19.5	3
33	48.0	42	48	31.0	11.5	19.5	3
35	49.2	44	50	31.0	11.5	19.5	3
38	52.3	49	56	31.0	14.0	22.0	4
40	55.5	51	58	31.0	14.0	22.0	4
43	57.5	54	61	31.0	14.0	22.0	4
45	58.7	56	63	31.0	14.0	22.0	4
48	61.9	59	66	31.0	14.0	22.0	4
50	65.0	62	70	32.5	15.0	23.0	4
53	68.2	65	73	32.5	15.0	23.0	4
55	70.0	67	75	32.5	15.0	23.0	4
58	71.7	70	78	37.5	15.0	23.0	4
60	74.6	72	80	37.5	15.0	23.0	4
63	79.0	75	83	37.5	15.0	23.0	4
65	84.1	77	85	37.5	15.0	23.0	4
68	87.3	81	90	34.5	18.0	26.0	4
70	87.3	83	92	42.0	18.0	26.0	4
75	95.0	88	97	42.0	18.0	26.0	4
80	98.4	95	105	41.8	18.2	26.2	4
85	104.7	100	110	41.8	18.2	26.2	4
90	111.0	105	115	46.8	18.2	26.2	4
95	114.0	110	120	47.8	17.2	25.2	4
100	117.4	115	125	47.8	17.2	25.2	4