



### Çalışma Limitleri

d1	14 - 100 mm
p	25 bar(Max)
t	-20/+120 °C
Vg	15 m/s

### Yüzey Seçenekleri

**Döner Eleman:** Karbon, Silisyum Karbür , Tungsten Karbür  
**Sabit Eleman:** Seramik, Silisyum Karbür, Tungsten Karbür, Krom Nikel  
**Elastomerler:** Viton(FKM) ,EPDM ,NBR

### Çalışma Ortamı

Temiz Su, atık su, yağ ve orta dereceli asidik sıvı

## ÖLÇÜLER

d	D3	D6	D7	L3	L4	L8
14	24	21	25	23.0	12.0	12.8
16	26	23	27	23.0	12.0	12.8
18	32	27	33	24.0	13.5	14.5
20	34	29	35	24.0	13.5	14.5
22	36	31	37	24.0	13.5	14.5
24	38	33	39	26.7	13.3	14.3
25	39	34	40	27.0	13.0	14.0
28	42	37	43	30.0	12.5	13.5
30	44	39	45	30.5	12.0	13.0
32	46	42	48	30.5	12.0	13.0
33	47	42	48	30.5	12.0	13.0
35	49	44	50	30.5	12.0	13.0
38	54	49	56	32.0	13.0	14.0
40	56	51	58	32.0	13.0	14.0
43	59	54	61	32.0	13.0	14.0
45	61	56	63	32.0	13.0	14.0
48	64	59	66	32.0	13.0	14.0
50	66	62	70	34.0	13.5	14.5
53	69	65	73	34.0	13.5	14.5
55	71	67	75	34.0	13.5	14.5
58	78	70	78	39.0	13.5	14.2
60	80	72	80	39.0	13.5	14.2
63	83	75	83	39.0	13.5	14.2
65	85	77	85	39.0	13.5	14.2
68	88	81	90	39.0	13.5	14.2
70	89	83	92	45.5	14.5	15.2
75	96	88	97	45.5	14.5	15.2
80	104	95	105	45.0	15.0	15.7
85	108	100	110	45.0	15.0	15.7
90	114	105	115	50.0	15.0	15.7
95	118	110	120	50.0	15.0	15.7
100	124	115	125	50.0	15.0	15.7