



Çalışma Limitleri

d1 6 - 110 mm
p 10 bar (Max)
t -40/+200 °C
Vg 20 m/s

Yüzey Seçenekleri

Döner Eleman: Krom Nikel
Sabit Eleman: Karbon
Elastomerler: Viton(FKM) ,EPDM ,NBR

Çalışma Ortamı

Temiz Su, yağ

ÖLÇÜLER

d	D	D1	L	L1
6	12	13.1	15	4.5
8	16	17.1	15	5.5
10	20	18.1	15	5.5
12	22	20.6	18	5.5
14	24	23.1	22	6.0
15	24	26.9	22	7.0
16	26	26.9	23	7.0
17	26	26.9	23	7.0
18	32	30.9	24	8.0
19	32	30.9	25	8.0
20	34	30.9	25	8.0
22	36	35.4	25	8.0
24	38	35.4	27	8.0
25	39	38.2	27	8.5
26	39	38.2	27	8.5
28	42	43.3	29	9.0
30	44	43.3	30	9.0
32	46	43.3	30	9.0
33	47	53.5	39	11.5
35	49	53.5	39	11.5

d	D	D1	L	L1
38	54	60.5	39	11.5
40	56	60.5	39	11.5
42	57	60.5	39	11.5
45	61	65.5	41	11.5
48	64	65.5	41	11.5
50	66	72.5	45	11.5
55	71	72.5	47	11.5
60	80	79.3	49	11.5
65	85	84.5	51	11.5
70	90	89.5	51	11.5
75	99	94.5	57	11.5
80	104	99.5	59	11.5
85	109	105.5	59	13.5
90	114	111.5	62	13.5
95	119	116.5	62	13.5
100	124	119.5	75	13.5
110	143	132.2	75	17.5