



Çalışma Limitleri

d1	6-70 mm
p	6 bar(Max)
t	-20/+120 °C
Vg	10 m/s

Yüzey Seçenekleri

Döner Eleman: Karbon, Silisyum Karbür , Tungsten Karbür
Sabit Eleman : Seramik, Silisyum Karbür, Tungsten Karbür, Krom Nikel
Elastomerler: Viton(FKM) ,EPDM ,Nitril

Çalışma Ortamı

Temiz Su

ÖLÇÜLER

d	D3	D7	L3	L4
6	18	22	8.5	4
8	18	22	8.5	4
8	18	26	11	5.5/8
8	24	26	11	5.5/8
9	24	26	11	5.5/8
10	24	26	11	5.5/8
11	24	26	11	5.5/8
12	24	26	13	5.5
12	32	29.5/38	13	8
13	24	26	13	5.5
14	32	29.5/38	13	8
14	35	29.5/38	13	8
15	32	29.5/38	13	8
15	35	29.5/38	13	8
16	32	29.5/38	13	8
16	35	29.5/38	13	8
16	39	42	13	8
17	39	42	13	8
18	39	42	13	8
19	39	42	13	8
20	39	42	13	8
20	42	45	13	10
22	42	45	13	10
23	47	50	14	10
24	47	50	14	10
25	42	50	14	10
25	47	50	14	10
28	54	57	15	10
30	54	57	15	10
32	54	57	15	10
35	60	63	16	10
38	65	68	18	12
40	65	68	18	12
45	70	73	20	12
50	85	88	23	15
55	85	88	23	15
60	105	110	30	15
65	105	110	30	15
70	105	110	32	15